Data sheet
Universal storage truck-2 UNI /400X170/ 2(



The series model SV-2 predstavuje univerzálne riešenie for skladové and logistické operácie. The design combines durable polypropylénový wheel centre with rubber tread z thermoplastic elastomer, which guarantees non-marking operation and protection floors. Thanks to klznému bearing achieves vozík maintenance-free operation with nízkym valivým odporom, which uľahčuje manipuláciu aj during plnom zaťažení 200 kg. Zinc-plated vidlica increases resistance to corrosion v štandardných warehouse conditions. An ideal choice for prepravu nákladov v industrial, obchodných alebo warehouse priestoroch, where important reliability and gentleness k povrchom.

Specifications

Load	200 kg
Výška x šírka	1070x550 mm
Plošina - šírka x hĺbka	400x170 mm
Rozmer kolies	plné Ø 200 mm
Hmotnosť	10 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).