Data sheet
Universal storage truck-2 UNI /405X255/ 15



The series model SV-2 UNI disponuje pozinkovanou vidlicou and combines polypropylénový wheel centre with rubber tread z thermoplastic elastomer, which ensures quiet and gentle movement na citlivých floors. The design with klzným bearing eliminuje potrebu maintenance and increases resistance to zaťaženiu až do 150 kg. Thanks to the use of kvalitných materiálov is tento vozík suitable for univerzálne use v skladoch, workshops alebo logistics centrách, where provides reliable and efektívnu manipuláciu with nákladom.

Specifications

Load	150 kg
Výška x šírka	1120x510 mm
Plošina - šírka x hĺbka	405x255 mm
Rozmer kolies	nafukovacie Ø 260 mm
Hmotnosť	7 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).