Data sheet
Storage truck/Platform truck 200/300 AL



The design of this skladového vozíka uses hliníkový material for rám, which reduces celkovú weight and uľahčuje presun. Thanks to the use of dvoch pevných kolesí with klznými ložiskami ensures stability during zaťažení, while the dve swivel kolesá with ihličkovými ložiskami umožňujú plynulé and precise manoeuvring. Behúne z thermoplastic elastomer ponúkajú non-marking operation and high durability against wear, suitable for demanding operating podmienky. An ideal choice for logistické and skladové applications, where important efektivita and protection of floor surfaces.

Specifications

Load	200/300 (ručný/plošinový) kg
Výška rukoväte	1310/1030 (ručný/plošinový) mm
Rozmery plošiny	860/1086x306 (ručný/plošinový) mm
Rozmer	520x470x1310/520x1190x1030 palce
Veľkosť nožnej plochy	185x456 mm
Kolesá predné	2xXJ-260 mm
Kolesá zadné	2xNL125 mm
Hmotnosť	17 kg
Veľkosť balenia	1300x135x450 mm
Materiál	hliník

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).