Data sheet
Scissor low lift truck 1000/1150-540



The design of this nožnicového nízkozdvižného vozíka uses zinc-plated vidlicu, which ensures long-term protection pred koróziou and increases service life v demanding environments. Thanks to the use of kvalitných ložísk, including ihličkových and guľôčkových, achieves smooth and quiet operation with minimálnou údržbou. Tread z thermoplastic elastomer provides excellent trakciu and gentleness k podlahám, while the wheel centre z durable material guarantees stability and load capacity. An ideal choice for applications v logistike, výrobe and skladoch, where important reliability and efektívna manipulácia with nákladmi.

Specifications

Load	1000 kg
Min. výška zdvihu	85 mm
Max. výška zdvihu	800 mm
Koleso predné 2x - Ø x šírka	180x50/LU (liatina+polyuretán) mm
Koleso zadné 2x - Ø x šírka	75x50/LUZ (liatina+polyuretán) mm
Dĺžka lyžín	1150 mm
Celková šírka lyžín	540 mm
Celkový čas zdvihu (bez záťaže)	78 s
Hmotnosť	128 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).