Data sheet
Scissor low lift truck 1500/1100-520



The design of this nožnicového vozíka includes polypropylénový wheel centre and thermoplastic elastomérový tread, which spolu vytvárajú durable and quiet systém suitable for intenzívne load. Klzné bearing ensures smooth movement and long service life without the need for maintenance, while the zinc-plated vidlica increases durability against corrosion. Model is optimalizovaný for use v industrial and logistics priestoroch, where provides reliable manipuláciu with nákladom do 1500 kg and výšku zdvihu 1100 mm, thereby minimises wear floor and increases safety operation.

Specifications

Load	1500 kg
Min. výška zdvihu	85 mm
Max. výška zdvihu	800 mm
Koleso predné 2x - Ø x šírka	150x40/LU (liatina+polyuretán) mm
Koleso zadné 2x - Ø x šírka	75x50/LUZ (liatina+polyuretán) mm
Dĺžka lyžín	1100 mm
Celková šírka lyžín	520 mm
Hmotnosť	118 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).