Data sheet
Barrel forklift 500



The series model VV-VOZIK NA SUDY 500 uses konštrukčné riešenie with pozinkovanou vidlicou and termoplastickým elastomérovým behúňom, which minimises noise and protects podlahové krytiny. Klzné bearing ensures smooth movement without potreby mazania, while the robustný polypropylénový wheel centre resists zaťaženiu až 500 kg. An ideal choice for industrial and skladové priestory, where important manipulácia with bežnými sudmi and bezpečná operation.

Specifications

Load	500 kg
Výška zdvihu min./max.	1500 mm
Celkový čas zdvihu (bez záťaže)	30 s
Dĺžka vozíka	1170 mm
Šírka vozíka	890 mm
Výška vozíka	1970 mm
Koleso predné 2x - Ø x šírka	150x47/CPC (polyamid) mm
Koleso zadné 2x - Ø x šírka	80x36/CPC (polyamid) mm
Max. zaťaženie	500 kg
Hmotnosť	165 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).