Data sheet
Workshop mobile crane 1T



The series model dielenských pojazdných žeriavov uses kombináciu pozinkovanej vidlice and thermoplastic elastomérového tread, which ensures quiet and bezstopý movement, ideálny for interiérové applications. The design includes plain bearing, which minimises friction and allows long-term maintenance-free operation, zvyšujúc service life equipment. Thanks to the use of odolných materiálov is tento žeriav suitable for demanding dielenské prostredia, where provides reliable manipuláciu with bremenami do 1 tony, while protects podlahové surfaces pred poškodením.

Specifications

Load	1000 kg
Pozícia 1	1000 kg
Pozícia 2	900 kg
Pozícia 3	800 kg
Pozícia 4	700 kg
Dĺžka	1360 mm
Šírka	960 mm
Šírka lyžiny	50 mm
Výška lyžiny	155 mm
Rameno dole - poz. 4	400 mm
Rameno dole - poz. 1	615 mm
Pri zdvihnutom ramene 1	2225 mm
Pri zdvihnutom ramene 4	2475 mm
Hmotnosť	103 kg
Celková výška	1600 mm

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).