Data sheet
Low lift trucks 2500/1150/540 T LU/LUZ



The design of this nízkozdvižného vozíka uses polypropylénový wheel centre combined with durable rubber tread, which increases durability against wear and reduces hlukovú záťaž. Thanks to the use of klzných ložísk ensures maintenance-free operation and long service life, while zinc-plated vidlica contributes k ochrane against corrosion. An ideal choice for applications v industrial and warehouse priestoroch, where important gentleness k podlahám and efektívna manipulácia with nákladom.

Specifications

Load	2500 kg
Min. výška zdvihu	85 mm
Max. výška zdvihu	200 mm
Koleso predné 2x - Ø x šírka	180x50/LU (liatina+polyuretán) mm
Koleso zadné 4x - Ø x šírka	82x70/LUZ (liatina+polyuretán) mm
Dĺžka lyžín	1150 mm
Celková šírka lyžín	540 mm
Hmotnosť	78 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).