Data sheet
NV 2500/800 T LU/LUZ



The series model NV 2500/800 T LU/LUZ predstavuje špecializované riešenie for manipuláciu with nákladmi v obmedzených priestoroch. The design uses zinc-plated vidlicu and tread z thermoplastic elastomer, which is characterised by high durability against wear and chemicals. Thanks to the use of klzného bearing achieves vozík non-marking operation and minimises potrebu maintenance. An ideal choice for industrial and skladové prostredia, where important reliability and protection of floor surfaces.

Specifications

Load	2500 kg
Min. výška zdvihu	85 mm
Max. výška zdvihu	200 mm
Koleso predné 2x - Ø x šírka	200x50/LU (liatina+polyuretán) mm
Koleso zadné 4x - Ø x šírka	82x70/LUZ (liatina+polyuretán) mm
Dĺžka lyžín	800 mm
Celková šírka lyžín	520 mm
Hmotnosť	63 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).