Data sheet
Low lift trucks 2500/800 T CPC/CPZ



The design of this nízkozdvižného vozíka combines durable polypropylénový wheel centre with rubber tread z thermoplastic elastomer, thereby achieves high durability against wear and gentleness k povrchom. Use klzného bearing ensures maintenance-free operation with minimálnym trením, which increases service life and reduces hlučnosť. An ideal choice for industrial and skladové prostredia, where important reliability and ochrana floors, with možnosťou mounting and brake for bezpečnú manipuláciu with nákladom.

Specifications

Load	2500 kg
Min. výška zdvihu	85 mm
Max. výška zdvihu	200 mm
Koleso predné 2x - Ø x šírka	180x50/CPC (polyamid) mm
Koleso zadné 4x - Ø x šírka	82x70/CPZ (polyamid) mm
Dĺžka lyžín	800 mm
Celková šírka lyžín	450 mm
Hmotnosť	70 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).