Data sheet
Low lift trucks 2500/1150/540 T CPC/CPZ



The design of this nízkozdvižného vozíka combines durable polypropylénový wheel centre with rubber tread, thereby achieves high load capacity and gentleness k podlahám. Thanks to the use of klzného bearing ensures maintenance-free operation and long service life, while the zinc-plated vidlica increases durability against corrosion. An ideal choice for logistické and výrobné priestory, where important quiet operation and reliability during handling with nákladmi.

Specifications

Load	2500 kg
Min. výška zdvihu	85 mm
Max. výška zdvihu	200 mm
Koleso predné 2x - Ø x šírka	180x50/CPC (polyamid) mm
Dĺžka lyžín	1150 mm
Celková šírka lyžín	540 mm
Hmotnosť	78 kg
Koleso zadné 4x - Ø x šírka	82x70/CPZ (polyamid) mm

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).