Data sheet
NV 3000/1150/540 T LU/LUZ



The design of this nízkozdvižného vozíka includes polypropylénový wheel centre combined with rubber tread, which ensures durability and quiet operation v industrial environments. Use klzného bearing allows maintenance-free operation and long service life, while the thermoplastic elastomér v behúni contributes k šetrnosti k podlahe. An ideal choice for applications with high nosnosťou, where important reliability and minimálna maintenance.

Specifications

Load	3000 kg
Min. výška zdvihu	85 mm
Max. výška zdvihu	200 mm
Koleso predné 2x - Ø x šírka	180x50/LU (liatina+polyuretán) mm
Koleso zadné 4x - Ø x šírka	82x70 tandem/LUZ (liatina+polyuretán) mm
Dĺžka lyžín	1150 mm
Celková šírka lyžín	540 mm
Hmotnosť	90 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).