Data sheet
Aluminum platform trucks - RIBS/710x410 A





The PV series model AL REBRÁ uses hliníkovú konštrukciu with rebrami, which increases rigidity and durability vozíka during zachovaní nízkej hmotnosti, which uľahčuje manipuláciu and reduces únavu používateľa. Thanks to the use of hliníka is vozík durable to corrosion, suitable for vlhké alebo chemicky agresívne prostredia. The design with jedným madlom allows pohodlné ovládanie and stability during pohybe. An ideal choice for prepravu nákladov v industrial, warehouse alebo logistics aplikáciách, where important reliability and long service life.

Specifications

Load		150 kg
Rozložený /š x h x v/		710x410x965 mm
Zložený /š x h x v/		560x410x245 mm
Materiál		hliník
Rozmer kolies		Ø 100 mm
Hmotnosť		8 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).