Data sheet
Forklift 1000/1600 B SINGEL CPC/CPZ ECO



Thanks to the use of high-quality wheel centre and rubber tread tento vysokozdvižný vozík achieves vynikajúce operating vlastnosti. Klzné bearing ensures maintenance-free operation and long service life, while the thermoplastic elastomér v konštrukcii contributes k odolnosti to wear. Zinc-plated vidlica increases koróznu durability, which robí tento model ideálnou voľbou for industrial and skladové prostredia. Technické parametre including high-quality mounting and spoľahlivej brake ensure bezpečnú and efektívnu manipuláciu with nákladom.

Specifications

Load	1000 kg
Max. výška zdvihu	1600 mm
Šírka lyžiny	120 mm
Dĺžka lyžín	900 mm
Rozsah nastavenia lyžín	240-635 mm
Ťažisko	400 mm
Dĺžka vozíka	1420 mm
Šírka vozíka	750 mm
Výška vozíka	1990 mm
Rádius otáčania	1590 mm
Koleso predné 2x - Ø x šírka	180x50/CPC (polyamid) mm
Koleso zadné 2x - Ø x šírka	75x60/CPZ (polyamid) mm
Hmotnosť	185 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).