Data sheet
Forklift 1000/1200 TANDEM LU/LUZ



The design of this vysokozdvižného vozíka uses zinc-plated vidlicu, which increases durability against corrosion and predlžuje service life v demanding conditions. Tread z thermoplastic elastomer provides excellent priľnavosť and non-marking operation, thereby protects floor pred poškodením and reduces hlučnosť during pohybe. Klzné bearing ensures smooth and quiet movement without potreby pravidelnej maintenance, which zjednodušuje operation and reduces náklady. Thanks to týmto vlastnostiam is vozík suitable for intenzívne use v skladoch, production halls and logistics centrách, where important reliability and gentleness k prostrediu.

Specifications

Load	1000 kg
Min. výška zdvihu	85 mm
Max. výška zdvihu	1200 mm
Koleso predné 2x - Ø x šírka	150x50/LU (liatina+polyuretán) mm
Koleso zadné 4x - Ø x šírka	78x60/LUZ (liatina+polyuretán) mm
Dĺžka lyžín	1150 mm
Celková šírka lyžín	560 mm
Ťažisko	600 mm
Šírka lyžiny	160 mm
Čas zdvihu - štandard	80-85 s
Čas zdvihu - dvojitý zdvih	45-50 s
Hmotnosť	178 kg
Šírka vozíka	685 mm
Dĺžka vozíka	1630 mm
Výška vozíka	1610 mm

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).