Data sheet
Forklift 1500/2500 TANDEM CPC/CPZ



The design of this vysokozdvižného vozíka uses zinc-plated vidlicu for zvýšenú durability against corrosion, while wheel centre z thermoplastic elastomer and rubber tread zaisťujú optimálnu trakciu and quiet operation, suitable for citlivé prostredia. Use klzného bearing minimises friction, which vedie k dlhovejšej životnosti and spoľahlivej operation without the need for maintenance. An ideal choice for demanding skladové operácie, where important efektivita and protection of floor surfaces.

Specifications

Load	1500 kg
Max. výška zdvihu	2500 mm
Min. výška zdvihu	90 mm
Ťažisko	600 mm
Dĺžka lyžín	1150 mm
Celková šírka lyžín	560 mm
Šírka lyžiny	160 mm
Čas zdvihu - štandard	150-160 s
Čas zdvihu - dvojitý zdvih	100-110 s
Celková výška pri spustených lyžinách	1770 mm
Koleso predné 2x - Ø x šírka	150x50/CPC (polyamid) mm
Koleso zadné 4x - Ø x šírka	76x60/CPZ (polyamid) mm
Hmotnosť	330 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).