Data sheet
Electric forklift EVR-1600/4500/3 AC LI-ION



The series model EVR 1600/4500/3 AC Li-Ion uses pokročilú konštrukciu with pozinkovanou vidlicou and termoplastickým elastomérom v kritických komponentoch, which increases durability against wear. Klzné bearing ensures maintenance-free operation and long service life, while the mounting and brzdový systém are navrhnuté for precise control and safety during handling. Thanks to the use of Li-Ion batérie offers dlhú prevádzkovú dobu and quick nabíjanie, which ho robí vhodným for intenzívnu dennú operation v industrial and logistics centrách.

Specifications

Load	1600 kg
Pojazd	elektrický
Zdvih-typ	elektrický
Zdvih-výška	4500 mm
Typ zdvíhacích lyžín	triplex
Dĺžka lyžín	1150 mm
Celková šírka lyžín	570 mm
Ťažisko	600 mm
Akumulátor	24/210 V/Ah
Nabíjačka	24/30, externé V/A
Šírka vozíka	850 mm
Výška vozíka	2022 mm
Šírka pracovnej uličky	2303 mm
Hmotnosť vrátane batérie	1240 kg
Použitá technológia	stiredavá - AC

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity = 40%-70%).