Data sheet
Hydraulic jack with adjustable head 5t



The design of this hydraulického zdviháka includes zinc-plated vidlicu, which ensures high resistance to corrosion and mechanickému wear, thereby predlžuje service life equipment. The series model with nastaviteľnou hlavicou allows flexibilné and precise umiestnenie bremien, which increases safety and efektivitu during práci. Thanks to the use of kvalitných materiálov and dôkladnému spracovaniu, zdvihák provides reliable výkon during zaťažení do 5 ton, suitable for demanding applications v industrial workshops, skladoch alebo stavebných priestoroch. An ideal choice for úlohy vyžadujúce robustnosť and long-term durability.

Specifications

Load	5000 kg
Výška	197 mm
Max. výška	402 mm
Výška nastaviteľnej hlavice	80 mm
Hmotnosť	4 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).