Data sheet
Hydraulic jack with adjustable head 16t



The series model hydraulických zdvihákov with nastaviteľnou hlavicou 16t is designed for profesionálne use v industrial and stavebných environments. The design includes zinc-plated vidlicu, which increases durability against corrosion, and thermoplastic elastomérový tread, which minimises wear floor and reduces hlučnosť during pohybe. Thanks to kĺznému bearing ensures maintenance-free operation and long service life, which is an ideal choice for zdvíhanie and presúvanie ťažkých nákladov with presnosťou and bezpečnosťou. Tento zdvihák is suitable for use v workshops, skladoch and na stavbách, where potrebná vysoká load capacity and reliability.

Specifications

Load	16000 kg
Výška	242 mm
Max. výška	457 mm
Výška nastaviteľnej hlavice	70 mm
Hmotnosť	7,3 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).