# Data sheet
# Platform truck 850x500 - 1 handle 200 kg



The design of this plošinového vozíka uses zinc-plated vidlicu and thermoplastic elastomér v behúni, which increases durability and tichú operation. Thanks to the use of klzného bearing ensures maintenance-free operation and long service life, thereby minimises náklady na údržbu. Tento model is suitable for various prostredia, including industrial and komerčných priestorov, where important reliability and efektívnosť manipulácie with nákladom.

## Specifications

| | |
|---|---|
| Load | 200 kg |
| Šírka plošiny | 500 mm |
| Dĺžka plošiny | 850 mm |
| Výška rúčky od zeme | 940 mm |
| Materiál | impregnované drevo, plech |
| Rozmer kolies | Ø 125 mm |
| Hmotnosť | 16 kg |

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).