Data sheet
Plošinový vozík malý 630X400 SKLADACÍ 10



The PV series model malý 630x400 skladací is designed for efektívnu manipuláciu with nákladom do 100 kg v warehouse alebo production priestoroch. Thanks to the use of pozinkovanej vidlice achieves high resistance to corrosion, which predlžuje service life vozíka v demanding conditions. Tread z thermoplastic elastomer ensures quiet and non-marking operation, while saves floor surface. Konštrukcia uses plain bearing, which allows maintenance-free operation and reduces nároky na údržbu. An ideal choice for applications, where potrebná kompaktnosť and jednoduché skladovanie, napríklad v logistics centrách alebo during distribúcii tovaru.

Specifications

Load	100 kg
Rozmery plošiny	630x400 mm
Výška rúčky od zeme	900 mm
Rozmer vozíka po zložení	630x400x90 mm
Rozmer kolies	Ø 80 mm
Hmotnosť	8,5 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).