Data sheet
Little folding platform truck 705X440/150 kg



The design of this skladacieho plošinového vozíka uses zinc-plated vidlicu, which ensures durability against corrosion, and thermoplastic elastomérový tread, which minimises noise and saves podlahové surfaces. Thanks to the use of klzného bearing ensures maintenance-free operation and smooth movement, while the non-marking operation increases comfort during handling. Tento model is optimalizovaný for use v skladoch, workshops and kancelárskych environments, where important ľahká skladovateľnosť and reliability during preprave nákladov do 150 kg.

Specifications

Load	150 kg
Rozmery plošiny	705x440 mm
Výška rúčky od zeme	900 mm
Rozmer vozíka po zložení	705x440x90 mm
Rozmer kolies	Ø 80 mm
Hmotnosť	9,5 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).