Data sheet
Platform truck 1000x700-1 handle /XD160/



The design of this plošinového vozíka uses zinc-plated vidlicu for zvýšenú durability against corrosion, while wheel centre is made z durable material and tread z thermoplastic elastomer for tichú operation. Thanks to the use of ihličkového bearing ensures maintenance-free operation and long service life, while the mounting and brake are navrhnuté for bezpečnú manipuláciu with nákladom. Tento model is suitable for demanding prostredia, such as are industrial haly alebo sklady, where vyžaduje reliability and efektivita.

Specifications

Load	300 kg
Šírka plošiny	700 mm
Dĺžka plošiny	1000 mm
Výška rúčky od zeme	1005 mm
Materiál	impregnované drevo, plech
Rozmer kolies	Ø 160 mm
Hmotnosť	0 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).