Data sheet
P324 PU-K100

Swivel castor - mounting type: top plate.



The design of this wheel uses polyamide wheel centre, which is durable and lightweight, combined so šedým polyurethane tread for plynulé odvaľovanie and nízkú hlučnosť. Thanks to the use of high-quality bearing ensures maintenance-free operation and long service life. An ideal choice for applications v industrial alebo komerčných priestoroch, where important reliability and ochrana podkladu.

Wheel PU series:

Wheel:

- polyamide

Tread:

- grey polyurethane

Bracket:

- plastic

Specifications

Diameter (D)	100 mm
Wheel width (S)	70 mm
Plate size (A x B)	94x64 mm
Bolt hole spacing (a x b)	75x45 mm
Bolt holes Ø	8 mm
Offset (F)	28 mm
Mounting height(H)	138 mm
Load	80 kg
Bearing type	Klzné
Mounting type	Mounting bracket
Tread material	Polyuretán
Attributes	Non-marking
Farba behúňa	Sivá
Wheel centre colour	Prírodná biela
Wheel centre	Polyamide

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).