Data sheet
531 NL-V200C

Fixed castor - mounting type: top plate (4 bolt holes).



The design of this pevného rolovacieho castors uses montážnu dosku na four otvory (príruba) for spoľahlivé mounting. Thanks to the use of thermoplastic elastomer v behúni and durable wheel centre ensures tichú operation and protection floors. Klzné bearing allows maintenance-free operation, which is an ideal choice for industrial and komerčné prostredia, where vyžaduje smooth movement and long service life.

TREAD AND TYRE HARDNESS	90° ± 5° Shore A	
ROLLING RESISTANCE	satisfactory	●●○○○
OPERATING NOISE	very good	●●●●○
WEAR RESISTANCE	sufficient	●○○○○
TEMPERATURE RANGE	od -25 °C do +80 °C	

Specifications

Diameter (D)		200 mm
Wheel width (S)		46 mm
Plate size (A x B)		135 × 106 mm
Bolt hole spacing (a x b)		105 × 75 mm
Bolt holes Ø		11 mm
Mounting height(H)		235 mm
Load		150 kg
Bearing type		Ihlové
Mounting type		Mounting bracket
Tread material		Guma a TPE
Farba behúňa		Čierna
Wheel centre colour		Black
Wheel centre		Polypropylén

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).