Data sheet
551F NL-V075C

Swivel castor - mounting type: bolt hole, with brake.



The design of this rolovacieho castors uses polypropylénový wheel centre combined with rubber tread, which ensures non-marking operation and gentleness k podlahovým povrchom. Thanks to klznému bearing achieves maintenance-free operation with nízkym trením, while the zinc-plated vidlica increases resistance to corrosion. An ideal choice for applications v industrial, warehouse alebo kancelárskych priestoroch, where important stability and kontrola movement. Integrovaná brake allows precise pozicionovanie, and mounting hole na skrutku uľahčuje installation na various typy konštrukcií.

TREAD AND TYRE HARDNESS	90° ± 5° Shore A	
ROLLING RESISTANCE	satisfactory	●●○○○
OPERATING NOISE	very good	●●●●○
WEAR RESISTANCE	sufficient	●○○○○
TEMPERATURE RANGE	od -25 °C do +80 °C	

Specifications

Diameter (D)		75 mm
Wheel width (S)		23 mm
Priemer príruby vidlice		49 mm
Bolt hole Ø		10.5 mm
Offset (F)		32 mm
Mounting height(H)		96 mm
Load		40 kg
Bearing type		Ihlové
Mounting type		Stredový otvor
Tread material		Guma a TPE
Farba behúňa		Čierna
Wheel centre colour		Black
Wheel centre		Polypropylén
Typ brzdy		F

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).