Data sheet
NOB-g125/8 VP

Wheel.



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The series model NOB-g125/8 VP offers konštrukčné riešenie with polypropylene wheel centre durable against prasknutiu and svetlo-sivým farebným prevedením. Tread z thermoplastic rubber elastomer is non-detachably mechanicky combined with wheel centre, which guarantees a long service life and quiet operation without stopovania. Thanks to jedno radiálnemu ball bearing with cover and minábojom zakrytým thread guard cover achieves spoľahlivá and maintenance-free operation. This wheel is suitable for use v ľahkých manipulačných equipment, skladoch, small výrobách and prevádzkach, where vyžaduje gentleness k podlahe and quiet operation.

Wheel NOB series:

Wheel center:

- polypropylene
- impact resistant
- light-grey color

Tread:

- thermoplastic rubber elastomer
- chemically-bonded inseparable connection with the wheel center
- silent operation
- non-marking
- dark-grey color

Application:

- light-duty handling equipment
- suitable for warehouses, small productions and operations

Bearing - ball:

- one radial ball bearing with sealing covers
- wheel hub covered with a threaded guard

TREAD AND TYRE HARDNESS	85° ± 3° Shore A	●●●○○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	satisfactory	●●○○○
TEMPERATURE RANGE	from -20 °C to +60 °C	

Specifications

Diameter (D)	125 mm
Wheel width (S)	32 mm
Mounting height(H)	125 mm
Load	100 kg
Vnútorný priemer náboja (d)	8 mm
Dĺžka náboja (L)	36 mm
Bearing type	Ball
Tread material	Guma a TPE
Attributes	
Farba behúňa	Sivá
Wheel centre colour	Sivá
Wheel centre	Polypropylén

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).