Data sheet
CAZ-G082-70/20 /2600/ 6204 ZV 14-17/

Wheel.



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The series model CAZ predstavuje samostatné wheel with wheel centre vyrobeným z hliníkovej liatiny, which ensures high strength and durability. Tread is designed for use na čistých hladkých floors, such as aj na mierne znečistených povrchoch šponami and oils. Technické riešenie includes dve radiálne ball bearings with krytmi, which ensure plynulý chod, long service life and maintenance-free operation. Thanks to kombinácii durable material and high-quality bearing is toto wheel suitable for industrial and komerčné prostredia, where vyžaduje reliability and minimálna potreba maintenance. Konštrukcia allows efektívne fungovanie aj v demanding conditions, thereby increases produktivitu and safety operation.

Wheel CAZ series:

- die-cast aluminium

Použitie:

- clean, even floors and lines or floors soiled with metal chips and oil

Bearing - ball:

- two radial ball bearing with sealing covers

TREAD AND TYRE HARDNESS	180 – 220 HB	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	sufficient	●○○○○
WEAR RESISTANCE	excellent	●●●●●
TEMPERATURE RANGE	from -100 °C to +600 °C (bearing K)	
TEMPERATURE RANGE	from -20 °C to +120 °C (bearing G)	

Specifications

Diameter (D)		82 mm
Wheel width (S)		70 mm
Mounting height(H)		82 mm
Bearing type		Ball
Tread material		Kov
Wheel centre colour		Hliníková
Wheel centre		Hliníková liatina
Load		2600 kg

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).