Data sheet
KL-CU-g043/14/10

Separate pulley.



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design tejto samostatnej kladky series CU spočíva v spojení robustného wheel centre with rubber tread, which ensures non-marking operation and gentleness k podlahám. Thanks to the use of high-quality bearing (klzné/ihlové/ball) achieves kladka high durability and maintenance-free operation. Model is suitable for various industrial and komerčné prostredia, where important quiet and reliable movement. Zinc-plated vidlica contributes k dlhovekosti and odolnosti to corrosion, thereby increases service life celého systému.

Specifications

Diameter (D)	43 mm
Wheel width (S)	14 mm
Mounting height(H)	43 mm
Load	50 kg
Vnútorný priemer náboja (d)	10 mm
Bearing type	Ball
Farba behúňa	Žlto-Hnedá
Wheel centre colour	Black
Wheel centre	Oceľ

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).