Data sheet
CZC-GX200/20



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design of this wheel uses vstrekovaný teplotne durable polyamid, which is durable to vysokým temperatures and prasknutiu, which ho robí ideálnou voľbou for use v lakovniach alebo peciach with krátkodobou teplotou do +240°C. Thanks to dvom radiálnym nerezovým ball ložiskám with krytmi ensures maintenance-free operation and long service life. Teplota wheel by nemala prekročiť +150°C, while teplotná durability platí len during použití montážneho kompletu with teflónovým povrchom.

Wheel CZC series:

Injection heat-resistant polyamide:

- abrasion resistant
- natural white color

Application:

- paint shops
- oven temperature short-term up to +240°C
- wheel temperature must not exceed +150 °C

*temperature resistance only applies when using a teflon tube

Bearing - ball, stainless:

- two radial ball bearing with sealing covers

TREAD AND TYRE HARDNESS	85° Shore D	●●●●●
ROLLING RESISTANCE	excellent	●●●●●
OPERATING NOISE	satisfactory	●●○○○
WEAR RESISTANCE	good	●●●○○
TEMPERATURE RANGE	od -25 °C do +150 °C	

Specifications

Diameter (D)		200 mm
Load		900 kg
Vnútorný priemer náboja (d)		20 mm
Dĺžka náboja (L)		56 mm
Uloženie ložísk (L1)		41 mm
Bearing type		Ball
Tread material		Plastic
Attributes		Non-marking
Wheel centre colour		Krémová
Wheel centre		Polyamide
Wheel width (S)		50 mm

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).