Data sheet
RUZ-G075-60/20

Wheel.



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The series model RUZ is designed such as samostatné wheel with kovovým wheel centre and liatym polyuretánovým elastomérovým behúňom, which is non-detachably chemicky combined with wheel centre, which guarantees long-term durability and vrubovú húževnatosť. Thanks to the use of dvoch radiálnych guličkových ložísk with krytmi ensures plynulý and maintenance-free chod with nízkym rozbehovým and valivým odporom. The design with polyurethane tread provides dobrú elasticity and absorbciu vysokej záťaže, while is gentle k podlahám – nefarbí and nepoškodzuje ich. Toto wheel is primárne určené for nízkozdvižné and vysokozdvižné ručné trolleys v environments with rovným polyuretánovým povrchom, where combines reliability and efektívnosť.

Wheel RUZ series:

Wheel center:

- steel

Tread:

- casted polyurethane-elastomer
- chemically-bonded inseparable connection with the wheel center
- good elasticity and absorption of high load capacity
- notch toughness
- floor preservation and non-marking
- low level of starting and rolling resistance
- brown color

Application:

- flat polyurethane floors
- primarily intended for pallet trucks and forklift trucks

Bearing - ball:

- two radial ball bearing with sealing covers

TREAD AND TYRE HARDNESS	92° ± 3° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	excellent	●●●●●
TEMPERATURE RANGE	od -20 °C do +70 °C	

Specifications

Diameter (D)		75 mm
Wheel width (S)		60 mm
Mounting height(H)		75 mm
Load		410 kg
Vnútorný priemer náboja (d)		20 mm
Dĺžka náboja (L)		60 mm
Bearing type		Ball
Tread material		Polyuretán
Farba behúňa		Hnedá
Wheel centre colour		Black
Wheel centre		Oceľ

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).