Data sheet
RUZ-082-28

Wheel.



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The series model RUZ predstavuje samostatné wheel with kovovým wheel centre and liatym polyuretánovým elastomérovým behúňom, which are non-detachably chemicky spojené. Toto spojenie ensures excellent húževnatosť and durability, while polyuretánový tread provides excellent elasticity and schopnosť absorbovať high load. Thanks to svojim vlastnostiam wheel nepoškodzuje and nefarbí floor, which ho robí ideálnou voľbou for straight polyurethane surfaces. Nízky rozbehový and valivý odpor increases efektivitu práce, and preto is wheel primárne určené for nízkozdvižné and vysokozdvižné ručné trolleys.

Wheel RUZ series:

Wheel center:

- steel

Tread:

- casted polyurethane-elastomer
- chemically-bonded inseparable connection with the wheel center
- good elasticity and absorption of high load capacity
- notch toughness
- floor preservation and non-marking
- low level of starting and rolling resistance
- brown color

Application:

- flat polyurethane floors
- primarily intended for pallet trucks and forklift trucks

TREAD AND TYRE HARDNESS	92° ± 3° Shore A	●●●●○
ROLLING RESISTANCE	very good	●●●●○
OPERATING NOISE	good	●●●○○
WEAR RESISTANCE	excellent	●●●●●
TEMPERATURE RANGE	od -20 °C do +70 °C	

Specifications

Diameter (D)		82 mm
Wheel width (S)		28 mm
Mounting height(H)		82 mm
Load		850 kg
Vnútorný priemer náboja (d)		20 mm
Dĺžka náboja (L)		91 mm
Bearing type		-
Tread material		Polyuretán
Farba behúňa		Hnedá
Wheel centre colour		Black
Wheel centre		Oceľ

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).