Data sheet
HLU-200-50-60/20,1

Wheel.



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The series model HLU disponuje konštrukčným solution with vysoko durable wheel centre z tvárnených oceľových plechov, which is lakovaný sivou farbou for zvýšenú durability. Tread z liatého polyurethane elastomer is non-detachably chemicky combined with wheel centre, which ensures excellent elasticity and absorpciu vysokých záťaží. Thanks to vrubovej húževnatosti nepoškodzuje and nefarbí floor, while nízky rozbehový and valivý odpor zlepšuje manipuláciu. An ideal choice for tvrdé aj mäkké industrial floor with miernymi nerovnosťami, suitable for nepretržitú operation.

Wheel HLU series:

Disk:

- highly durable welded steel construction made of forged sheets
- lacquered, grey color

Tread:

- casted polyurethane elastomer
- chemically-bonded inseparable connection with the wheel center
- good elasticity, good at preserving floor surfaces
- high abrasion resistance
- non-marking
- low level of starting and rolling resistance
- brown color

Application:

- hard and soft industrial floor surfaces
- mild obstacles
- continuous operation

Specifications

Diameter (D)	200 mm
Wheel width (S)	50 mm
Mounting height(H)	200 mm
Load	900 kg
Vnútorný priemer náboja (d)	20,1 mm
Dĺžka náboja (L)	60 mm
Bearing type	-
Tread material	Polyuretán
Attributes	Non-marking
Farba behúňa	Žlto-Hnedá
Wheel centre colour	Sivá
Wheel centre	Šedá liatina

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).