Data sheet
Top plate 624x2

Swivel castor - mounting type: top plate (4 bolt holes).



VYROBENÉ
NA SLOVENSKU
MADE IN SLOVAKIA

The design točného castors series 624x2 uses robustný wheel centre and elastický rubber tread, which minimises noise and protects floor pred poškodením. Klzné bearing v jadre castors allows plynulú rotáciu without potreby mazania, thereby reduces údržbu and increases reliability v demanding conditions. An ideal choice for industrial and skladové prostredia, where important durability and quiet operating výkon, with možnosťou mounting cez montážnu dosku for stable installation.

Specifications

Plate size (A x B)	135x110 mm
Bolt hole spacing (a x b)	105x80/75 mm
Bolt holes Ø	11 mm
Mounting height(H)	30 mm
Load	400 kg
Bearing type	Ball
Mounting type	Mounting bracket

When choosing the right wheel, please note the technical conditions and step-by-step guide in our catalogue (p. 4-17) or visit our website https://sk.renost.net/en/. Note: Load capacity refers to dynamic load according to STN EN 12532 (speed: 4 km/h, height of obstacles = 2,5% of the wheel diameter for tread hardness ≥ 90° Shore; height of obstacles = 5,0% of the wheel diameter for tread hardness < 90° Shore; temperature 17°C-23°C; humidity= 40%-70%).